



ATX 450W Chieftec GPA-450S8

35,00 USD

Preturile pe acest site nu
contin TVA

Seria **Arena** este **destinata** in special sistemelor de **office sau home cinema**. **Active PFC** si **eficienta** de peste **80%** asigura **putere constanta** in **orice conditii**. **Ventilatorul silentios** de 120 mm asigura o racire adecvata fara zgomot. **Un raport calitate pret excelent!**

General

| | |
|------------------------|--------------------------------|
| Tip | ATX |
| Format | PS2 |
| Dimensiuni | 140 mm x 150 mm x 87 mm |
| Tensiune de alimentare | 100V~120V 8A, 220V~240V 4A |
| Frecventa | 47-63 Hz |

Caracteristici de putere

| | |
|-------------------------|-------|
| Putere maxima teoretica | 450 W |
| PFC | Activ |
| Eficienta minima | 80 % |

Parametri in sarcina maxima

| | |
|----------------------------|----------|
| Amperaj maxim +5V | 18A x 1 |
| Amperaj maxim +3.3V | 22A x 1 |
| Amperaj maxim +12V | 21A x 4 |
| Amperaj maxim -12V | 0.3A x 1 |
| Amperaj maxim +5V Stand By | 2.5A x 1 |

Conectica si racire

| | |
|-------------------------------|---|
| Dual Processor Ready (EPS12V) | Nu |
| Conectori tip fix | 1 x 20/24 Pin ATX |
| Conectori tip modular | 3 x SATA, 1 x Floppy, 1 x 6 Pin PCIe, 2 x HDD |
| Ventilatoare | 1 x 120 mm Silent Fan (25~39 dB) |
| Control al turatiei automat | Da |
| Cable tube | Da |

Funcții speciale

| | |
|-----------|---|
| Protecție | OVP, OCP, OTP Tensiune, Curent, Temperatura |
|-----------|---|

Altele

| | |
|----------|---------|
| Garantie | 36 luni |
|----------|---------|

Pagina produsului:

<http://www.maguay.ro/produse/ac-power/surse/atx-450w-chieftec-gpa-450s8-l1043>

Document creat la data de:

26 Aprilie 2024 la ora 19:26